



Upright cold water high-pressure cleaner. Pressure switch control, Easy-Press trigger gun with soft grip surface, pivoting stainless steel spray lance, detergent tank, separate compartment for nozzles.



1 Proven Kärcher quality

- Four-pole, water-cooled electro motor.
- Robust brass cylinder head and ceramic piston.

2 Hose storage

- Mounted on both sides; for 20 m high-pressure hose.
- Hose guide under the device; high safety against tilting.

3 For increased safety

- Integrated electronics system for machine monitoring.
- Switch-off in the case of overvoltage or low voltage range.

4 Outstanding mobility

- Large rubberised wheels for uneven surfaces, stairs and half landings.
- Tried-and-tested sack truck principle for easy, ergonomic transport.



HD 10/23-4 S

- Water-cooled three-phase motor
- Equipped with the Kärcher power nozzle
- Easy Press spray gun with soft grip and servo control

Technical data

| | | |
|-------------------------------|---------------|------------------|
| Order No. | 1.286-309.0 | |
| EAN code | 4039784732735 | |
| Current type | Ph / V / Hz | 3 / 400 / 50 |
| Flow rate | l/h | 1000 |
| Working pressure | bar / MPa | 230 / 23 |
| Max. pressure | bar / MPa | 253 / 25.3 |
| Max. feed temperature | °C | 60 |
| Connected load | kW | 7.8 |
| Weight | kg | 62 |
| Dimensions (L x W x H) | mm | 560 × 500 × 1090 |
| Cleaning agent tank | l | 6 |

Equipment

| | | |
|--|------------------------|------|
| Spray gun | Easy Press trigger gun | |
| Spray gun with soft grip | ■ | |
| High-pressure hose | m | 10 |
| Spray lance | mm | 1050 |
| Power nozzle | ■ | |
| Anti-twist system | ■ | |
| 4-pole three-phase motor with air and water cooling | ■ | |
| Pressure switch-off | ■ | |
| Large fine mesh water filter | ■ | |
| Oil sight glass | ■ | |
| Servo control | - | |
| Brass water inlet fitting | ■ | |

■ Included in delivery.