



PVC BRAID REINFORCED HOSE



Applications

- Water supply and draining for equipment.
- Transfer of various fluids and powder.
- Supplying water ,gas ,oil etc in agriculture and industry.
- Other special purpose.

Characteristic

- Durable , anti-cold proof , non-inflated.
- High-flexibility , light-weight and easy to handle.
- No fissure phenomenon by ultraviolet rays and direct rays of the sun.
- Little expansion or contraction.
- Low cost , economical.
- Temperatures:-5°C To+65°C.

1

Model number	Specification inch	I.DxO.D mm		Length m	W.P Bar	B.P Bar	Weight Kg/Roll	Bend Radius	Dim. mm
MPG04	5/32	4	9	100	12	70	6.0	17	330x130
MPC06	1/4	6	10	100	8	45	6.0	25	350x150
MPG06	1/4	6	11	100	10	65	8.0	25	360x150
MPC08	5/16	8	12	100	7	40	7.5	33	400x160
MPG08	5/16	8	13	100	10	58	10.0	33	420x160
MPG09	3/8	9	14	100	10	48	11.0	38	450x170
MPC10	3/8	10	14	100	5	35	9.0	40	430x180
MPG10	3/8	10	15	100	9	45	12.0	40	460x170
MPC12	1/2	12	16	100	7	30	11.0	50	490x180
MPG12	1/2	12	17	100	8	43	14.0	48	490x180
MPC13	1/2	13	17	100	5	30	11.5	52	500x180
MPG13	1/2	13	18	100	8	40	15.0	52	500x180
MPC15	5/8	15	19	100	5	28	13.0	63	580x160
MPG15	5/8	15	20	100	8	35	17.0	60	570x200
MPC16	5/8	16	20	100	5	28	14.0	67	580x200
MPG16	5/8	16	21	100	8	35	18.0	64	580x200
MPC19	3/4	19	24	50	4	25	10.0	80	560x150
MPG19	3/4	19	25	50	8	32	12.5	76	560x150
MPC25	1	25	30	50	4	23	13.5	105	680x220
MPG25	1	25	31	50	6	28	15.0	100	680x220
MPC32	1-1/4	32	38	50	3.5	18	20.5	133	840x200
MPG32	1-1/4	32	39	50	5	26	25.0	128	840x200
MPC38	1-1/2	38	45	40	3.5	15	22.5	155	900x200
MPG38	1-1/2	38	46	40	5	20	26.0	152	910x200
MPC50	2	50	59	40	3	13	38.0	205	1100x240
MPG50	2	50	60	40	4	17	40	200	1130x250