

CRT 36 Ride-on Trowels



The better choice for finishing concrete surfaces: CRT 36

The ride-on trowels of the CRT 36 range feature a finishing diameter of 915 mm and are characterized by high productivity and user comfort. One person can easily and simply operate the practical, integrated wheel set from the rear. There are no annoying additional controls at the front. That means the operator has more freedom when using the device.

- Optimum maneuverability thanks to its balanced power-to-weight ratio
- Sensitive, ergonomically designed 2-lever controls
- Variable coupling: For constant engine torque at low and high rotor speeds
- Good visibility thanks to front and rear lights as standard especially on night operations



Integrated wheel set

The integrated wheel set makes changing the blades quick and easy.



Technical specifications

CRT 36

	CRT 36-24A	CRT 36-24A-WK
L x W x H Shipping mm	2,032 x 1,041 x 1,372	2,184 x 1,143 x 1,613
L x W x H Operating mm	2,032 x 1,041 x 1,372	2,032 x 1,041 x 1,372
Weights		
Operating weight kg	392	395
Troweling diameter mm	915	915
Quantity of blades	8	8
Blades mm	355 x 152	355 x 152
Combination blades mm	355 x 203	355 x 203
Combination blades mm	355 x 254	355 x 254
Pitch range °	0 - 25	0 - 25
RPM area rpm	25 - 165	25 - 165
Engine / Motor	Air-cooled two-cylinder four-cycle gasoline engine	Air-cooled two-cylinder four-cycle gasoline engine
Engine / Motor manufacturer	Honda	Honda
Displacement cm ³	670	720
Operating performance kW (hp)	18 (24)	18.6(25)
RPM / speed Operating rpm	3,850	3,850
Fuel type	Unleaded Gasoline	Unleaded Gasoline
Fuel consumption I/h	9	9
Tank capacity Fuel I	24.6	24.6

Please note

that product availability can vary from country to country. It is possible that information / products may not be available in your country. More detailed information on engine power can be found in the operator's manual; the stated power may vary due to specific operating conditions. Subject to alterations and errors excepted. Applicable also to illustrations. Copyright © 2015 Wacker Neuson SE.