

HOSE REELS FOR COMPRESSED AIR, SERIES EASY ROLLER



Automatic rewind, spring-driven hose reel, with plastic enclosure (made of nylon and polypropylene) and pivoting wall bracket, suitable for the use with compressed air and water (temperature range: $-10^{\circ}\text{C} - +60^{\circ}\text{C}$) and for hoses of 8 x 12 mm (or 10 x 14 mm) with a max. length of 15 m (or 10 m). Inlet connection air: 1/4" BSP. Max working pressure: 20 bar.

The standard colour of the enclosure is red with yellow cover. Also available in blue with red cover or in dark grey.



Art. no. 9400+3610

Automatic rewind, spring-driven hose reel, series "Easy Roller", with polyurethane hose 8×12 mm and 10 m length. Standard connection threads 1/4" BSP.

Art. no. 9400+3615

Automatic rewind, spring-driven hose reel, series "Easy Roller", with polyurethane hose 8×12 mm and 15 m length. Standard connection threads 1/4" BSP.

Art. no. 9408

Automatic rewind, spring-driven hose reel, series "Easy Roller", with polyurethane hose 10 x 14 mm and 10 m length. Standard connection threads 3/8" BSP.

Art. no.	Hose length	Hose diameter	Connection threads	Max working pressure	Weight	Dimensions (LxWxH) (mm)
9400+3610	10 m	8 x 12 mm	1/4" BSP (M)	20 bar	8,1 Kg	220x310x380
9400+3615	15 m	8 x 12 mm	1/4" BSP (M)	20 bar	8,2 Kg	220x310x380
9408	10 m	10 x 14 mm	3/8" BSP (M)	20 bar	8,2 Kg	220x310x380







HOSE REELS FOR COMPRESSED AIR, SERIES EASY ROLLER



Art. no. 9405

Automatic rewind, spring-driven hose reel, series "Easy Roller", with shaft and swivel in stainless steel AISI 303, pivoting wall bracket and 10 m – rubber hose 1/4" SAE 100 R1T.

Suitable for applications with a pressure up to 100 bar.

Standard colour blue, on demand also available in red.

Art. no.	Hose length	Hose diameter	Connection threads IN - OUT	Max working pressure	Weight	Dimensions (LxWxH) (mm)
9405	10 m	1/4"	1/2"BSP (M) – 1/4"BSP (F)	100 bar	10 kg	220x310x380



Art. no. **9409**

Automatic rewind, spring-driven hose reel, series "Easy Roller", with shaft and swivel in stainless steel AISI 303, pivoting wall bracket and 5 m - low pressure synthetic rubber hose 1/2" (ø int. 13 mm x ø ext. 23 mm), suitable for the use with water (-30°C - +110°C).

The hose meets FDA food industry standards and thus is suitable for food industry applications.

Standard colour blue, on demand also available in red.

Art. no.	Hose length	Hose diameter	Connection threads IN - OUT	Max working pressure	Weight	Dimensions (LxWxH) (mm)
9409	5 m	1/2"	1/2"BSP (M) – 1/2"BSP (F)	15 bar	9 kg	220x310x380

